

5MP IP IR MOTORIZED BULLET CAMERA

PEAKIPBC5MVAF

PEAK
PRODUCTS



*Featuring Sony Starvis
back illuminated CMOS
Sensor, 5MP, 4MP, & 1080P
streams, WDR, IR-Cut, Smart
IR, IP66, 12VDC & POE*

Features/Specs:

Image Sensor: 1/2.8" SONY Starvis Back-Illuminated CMOS Sensor

Resolution: 5MP

Compression: H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG

Minimum Illumination: 0.01Lux

S/N Ratio: ≥ 52dB

Scanning System: Progressive

Focus Length: 2.7-13.5mm

Infrared Distance: 40M

Ethernet: RJ45 (10/100Base-T)

Protocol: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP

ONVIF: Support ONVIF 2.4

Housing: Metal, IP66

Anti-cut Bracket: Yes

IR Cut Filter: Yes

Operation Temperature: -20°C ~ +60°C RH95% Max

Power Source: DC12V±10%, 950mA

SDI is not responsible for any errors or omissions in product specifications and does not warrant said specifications. Specifications can change without notification and some products may not appear as shown.

www.sdilink.com

PEAK
PRODUCTS